Yellow Card[™]

LEIMEI ACRYLIC (DONGGUAN) CO LTD

5 Long Tian Rd Gaoli Industrial Zone Tangxia Dongguan, Guangdong Sheng 523726 China

PT GLAS

Polymethyl Methacrylate (PMMA), sheets



File Number: E333090

Flame Rating 1.5 mm, ALL HB UL 94 3.0 mm, ALL HB UL 94 3.0 mm, ALL HB40 IEC 60695-11-10, -20 1.5 mm, ALL HB75 IEC 60695-11-10, -20 Thermal Value Test Method RTI Elec UL 746B 1.5 mm 50.0 °C 3.0 mm 50.0 °C 3.0 mm 50.0 °C RTI Istr UL 746B 1.5 mm 50.0 °C 3.0 mm 50.0 °C 3.0 mm 50.0 °C	Flammability	Value	Test Method
3.0 mm, ALL HB UL 94 3.0 mm, ALL HB40 IEC 60695-11-10, -20 1.5 mm, ALL HB75 IEC 60695-11-10, -20 Thermal Value Test Method RTI Elec UL 746B 1.5 mm 50.0 °C RTI Imp UL 746B 1.5 mm 50.0 °C 3.0 mm 50.0 °C RTI Str UL 746B 1.5 mm 50.0 °C	Flame Rating		
3.0 mm, ALL HB40 IEC 60695-11-10, -20 1.5 mm, ALL HB75 IEC 60695-11-10, -20 Thermal Value Test Method RTI Elec UL 746B 1.5 mm 50.0 °C RTI Imp UL 746B 1.5 mm 50.0 °C 3.0 mm 50.0 °C RTI Str UL 746B 1.5 mm 50.0 °C	1.5 mm, ALL	НВ	UL 94
1.5 mm, ALL HB75 IEC 60695-11-10, -20 Thermal Value Test Method RTI Elec UL 746B 1.5 mm 50.0 °C 3.0 mm 50.0 °C 1.5 mm 50.0 °C 3.0 mm 50.0 °C RTI Str UL 746B 1.5 mm 50.0 °C	3.0 mm, ALL	НВ	UL 94
Thermal Value Test Method RTI Elec UL 746B 1.5 mm 50.0 °C 3.0 mm 50.0 °C RTI Imp UL 746B 1.5 mm 50.0 °C 3.0 mm 50.0 °C RTI Str UL 746B 1.5 mm 50.0 °C	3.0 mm, ALL	HB40	IEC 60695-11-10, -20
RTI Elec UL 746B 1.5 mm 50.0 °C 3.0 mm 50.0 °C RTI Imp UL 746B 1.5 mm 50.0 °C 3.0 mm 50.0 °C RTI Str UL 746B 1.5 mm 50.0 °C	1.5 mm, ALL	HB75	IEC 60695-11-10, -20
1.5 mm 50.0 °C 3.0 mm 50.0 °C RTI Imp UL 746B 1.5 mm 50.0 °C 3.0 mm 50.0 °C RTI Str UL 746B 1.5 mm 50.0 °C	Thermal	Value	Test Method
3.0 mm 50.0 °C RTI Imp UL 746B 1.5 mm 50.0 °C 3.0 mm 50.0 °C RTI Str UL 746B 1.5 mm 50.0 °C	RTI Elec		UL 746B
RTI Imp UL 746B 1.5 mm 50.0 °C 3.0 mm 50.0 °C RTI Str UL 746B 1.5 mm 50.0 °C	1.5 mm	50.0 °C	
1.5 mm 50.0 °C 3.0 mm 50.0 °C RTI Str UL 746B 1.5 mm 50.0 °C	3.0 mm	50.0 °C	
3.0 mm 50.0 °C RTI Str UL 746B 1.5 mm 50.0 °C	RTI Imp		UL 746B
RTI Str UL 746B 1.5 mm 50.0 °C	1.5 mm	50.0 °C	
1.5 mm 50.0 °C	3.0 mm	50.0 °C	
	RTI Str		UL 746B
3.0 mm 50.0 °C	1.5 mm	50.0 °C	
	3.0 mm	50.0 °C	